

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 49 E.

CHAINS	
	<p>S. 89° 54' W., along the S. bdy. of sec. 32.</p> <p>Over rolling mountainous land; through scattered sagebrush and native grass; desc. 320 ft. over W. slope.</p>
16.50	Ravine, drains S.; asc. 100 ft. over SE. slope to the standard $\frac{1}{4}$ sec. cor.
27.30	Wash, 10 lks. wide, 1 ft. deep, drains S.
31.20	Trail road, bears N. and S.
40.25	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R49E <u>¼ S 32</u> 1970</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Ascend 300 ft. over broken and ledgy SE. slope.</p>
60.00	Spur, slopes SW.; desc. 140 ft. over W. slope.
75.50	Ravine, drains S.; asc. 60 ft. over E. slope.
80.50	<p>Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R49E <u>S 31 S 32</u> 1970</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>S. 89° 54' W., along the S. bdy. of sec. 31.</p> <p>Over rolling mountainous land, through scattered sagebrush and native grass; asc. 150 ft. over E. slope.</p>
9.00	Ridge, bears N. and S.; desc. 240 ft. over W. slope.
34.30	Draw, drains SW.; asc. 30 ft. over SE. slope.
36.00	Spur, slopes S.; desc. 30 ft. over SW. slope.