

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH R. 48 E.

<p>CHAINS 39.95</p>	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented with an old circular mound of stone; this position is harmoniously related to other existing corners found along this line and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R48E <u>$\frac{1}{4}$ S 33</u></p> <p style="text-align: center;">1970</p> <hr style="width: 20%; margin: auto;"/>
<p>6.50</p>	<p>S. $89^{\circ} 59'$ W., beginning new measurement.</p> <p>Over mountainous land, through scattered sagebrush and native grass; asc. 90 ft. over SE. slope.</p>
<p>40.04</p>	<p>Ridge, bears NE. and SW.; desc. 480 ft. over W. slope.</p> <p>Point for the standard cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R48E <u>S 32 S 33</u></p> <p style="text-align: center;">1970</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
<p>3.00</p>	<p>S. $89^{\circ} 59'$ W., along the S. bdy. of sec. 32.</p> <p>Over rolling land, through scattered sagebrush and native grass; desc. 50 ft. over W. slope.</p>
<p>14.00</p>	<p>Wash, 20 lks. wide, 4 ft. deep, drains N.; asc. 60 ft. over E. slope.</p>
<p>24.00</p>	<p>Low ridge, bears N. and S.; desc. 70 ft. over W. slope.</p>
<p>38.50</p>	<p>Wash, 10 lks. wide, 2 ft. deep, drains N.; asc. 110 ft. over E. slope.</p>
<p></p>	<p>Low ridge, bears N. and S.; desc. 10 ft. over W. slope.</p>