

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH R. 48 E.

CHAINS	
40.04	<p>Point for the standard $\frac{1}{2}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R48E <u>$\frac{1}{2}$ S 32</u></p> <p style="text-align: center;">1970</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Descend 300 ft. over W. slope.</p>
67.20	<p>Wash, 20 lks. wide, 4 ft. deep, drains NNW.; desc. gradually.</p>
75.80	<p>Ravine, drains N.; asc. 50 ft. over E. slope.</p>
80.08	<p>The standard cor. of secs. 31 and 32, monumented with an unmarked basalt stone, 16x16x5 ins., firmly set in a mound of stone; this position is harmoniously related to other existing corners found on this line and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R48E <u>S 31 S 32</u></p> <p style="text-align: center;">1970</p> <p><u>bury the unmarked stone alongside the iron post.</u></p>
	<p>N. $89^{\circ} 21'$ W., along the S. bdy. of sec. 31.</p> <p>Over rolling land, through scattered sagebrush and native grass; asc. 230 ft. over E. slope.</p>
21.50	<p>Ridge, bears N. and S.; desc. 320 ft. over W. slope.</p>
38.60	<p>Ravine, drains N.; asc. 10 ft. over E. slope.</p>
39.95	<p>Point for the standard $\frac{1}{2}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>