

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH R. 47 E.

CHAINS	
	<p style="text-align: center;">SC T41N R47E <u>½ S 34</u></p> <p style="text-align: center;">1970</p> <p>Over rolling land; desc. 120 ft. to the standard sec. cor.</p> <p>50.70 Trail road, bears NNW. and SSE.</p> <p>67.50 Wash, 10 lks. wide, 1 ft. deep, drains N.</p> <p>79.90 Wash, 10 lks. wide, 1 ft. deep, drains N.</p> <p>80.84 The standard cor. of secs. 33 and 34, monumented with a sandstone, 12x12x10 ins., mkd. with 3 grooves on the E. and W. faces, and firmly set in the ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R47E <u>S 33 S 34</u></p> <p style="text-align: center;">1970</p> <p>bury the original corner stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>S. 89° 43' W., along the S. bdy. of sec. 33.</p> <p>Over rolling land, through scattered sagebrush and native grass; desc. 40 ft. over W. slope.</p> <p>7.30 Wash, 10 lks. wide, 1 ft. deep, drains N.; asc. 50 ft. over E. slope.</p> <p>18.20 Low ridge, bears N. and S.; desc. 100 ft. over W. slope.</p> <p>39.86 The standard ¼ sec. cor. of sec. 33, monumented with the decayed remains of a wooden post loosely set in an old mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R47E <u>¼ S 33</u></p> <p style="text-align: center;">1970</p> <p>reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>