

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH R. 47 E.

CHAINS	
40.85	<p>The standard cor. of secs. 31 and 32, monumented with a basalt stone, 10x10x7 ins., mkd. with 5 grooves on the E. face and 1 groove on the W. face, firmly set in the ground, and a badly decayed wooden post with illegible scribe marks lying alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R47E <u>S 31 S 32</u></p> <p style="text-align: center;">1970</p> <p>bury the original corner stone and wooden post alongside the iron post, and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p>
	<p>S. 89° 53' W., along the S. bdy. of sec. 31.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p>
22.60	Trail road, bears N. and S.
37.70	Wash, 15 lks. wide, 3 ft. deep, drains N.
42.02	<p>Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R47E <u>¼ S 31</u></p> <p style="text-align: center;">1970</p> <p>raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p> <p>Continue over gently rolling land.</p>
64.00	Small wash, drains N.
84.04	<p>The standard cor. of Tps. 41 N., Rs. 46 and 47 E., monumented with a basalt stone, 10x8x4 ins., mkd: with 6 notches on the E. and W. edges, and firmly set in a mound of stone.</p> <p>At the corner point</p>