DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF R. 46 E.

	. THROUGH A PORTION OF R. 46 E.
CHAINS	
	SC
j	T41N R46E
	S 33 S 34
	1970
	bury the original corner stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	S. 89° 58' W., along the S. bdy. of sec. 33.
	Over gently rolling land, through scattered sagebrush and native grass.
40.17	Point for the standard ½ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	SC
1	T41N R46E
\$	½ S 33
	1970
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Continue over gently rolling land.
80.34	The standard cor. of secs. 32 and 33, monumented with a basalt stone, 12x9x7 ins., mkd. with 4 grooves on the E. face and 2 grooves on the W. face, and firmly set in a mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	SC
	T41N_R46E
	S 32 S 33
	1970
	bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
İ	
1	
I	
1	
1	
1	
1	
l	
l	i