

DEPENDENT RESURVEY OF THE WEST BOUNDARY OF
T. 40 N., R. 47 E.

CHAINS

N. 0° 06' W., bet. secs. 7 and 12.

Over rolling hills, through medium sagebrush and native grass; desc. 90 ft. over rolling N. slope to the $\frac{1}{4}$ sec. cor.

27.20 Draw, drains NW.

39.99 The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with a badly deteriorated wooden post with illegible scribe marks, and set in an old circular mound of stone.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T40N
R46E R47E
 $\frac{1}{4}$
S 12 | S 7

1970

bury the remains of the wooden post alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

N. 0° 19' E., beginning new measurement.

Over gently rolling land, through medium sagebrush and native grass.

40.05 The cor. of secs. 1, 6, 7 and 12, monumented with a basalt stone, 22x10x6 ins., mkd. with 5 grooves on the S. face, and 1 groove on the N. face, and firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N
R46E R47E
S 1 | S 6
S 12 | S 7

1970

bury the original cornerstone alongside the iron post, and raise a mound of stone, 5 ft. base, 3 ft. high, W. of cor.

N. 12° 15' E., bet. secs. 1 and 6.

Over rolling land, through scattered sagebrush and native grass; asc. 230 ft. along W. slope.