

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF  
T. 40 N., R. 47 E.

CHAINS	
6.00	Ridge, bears NNW. and SSE.; desc. 200 ft. over NE. slope.
15.30	Ravine, drains NE.; asc. 50 ft. over S. slope.
24.20	Spur, slopes E.; desc. 40 ft. over N. slope.
27.60	Draw, drains E.; asc. 90 ft. over S. slope.
40.31	The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a basalt stone, 14x10x10 ins., mkd. $\frac{1}{4}$ on the W. face, and firmly set in the ground with a mound of stone, W. of cor.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T40N R47E
	$\frac{1}{4}$
	S 2   S 1
	1970
	bury the original cornerstone alongside the iron post, and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	From this corner, a spring, bears S. $53^{\circ}$ W., 27.90 chs. dist.
	From this same corner, a spring, bears S. $77^{\circ}$ W., 9.60 chs. dist.
	N. $14^{\circ} 16'$ E., beginning new measurement.
	Over rolling hills, through scattered sagebrush and native grass; asc. 220 ft. over SE. slope.
31.70	Ridge, bears E. and W.; desc. 500 ft. over rolling land to the closing cor.
79.15	Spring, bears E., 0.35 chs. dist.
88.00	Trail road, bears NE. and SW.
107.50	Reservoir, bears N. $71^{\circ}$ E., 17.10 chs. dist.
113.90	Draw, drains E.
153.00	Draw, drains NW.
162.71	Intersect the Eighth Standard Parallel North.
	Point for the closing cor. of secs. 1 and 2 at proportionate dist.; there is no remaining evidence of the original cor.