

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF  
T. 40 N., R. 48 E.

CHAINS	
	N. 0° 11' E., beginning new measurement.
	Over rolling E. slope.
5.40	Wash, 10 lks. wide, 2 ft. deep, drains SE.
11.00	Spur, slopes SE.; desc. along E. slope.
20.10	Trail road, bears NW. and SE.
25.60	Wash, 10 lks. wide, 1 ft. deep, drains ESE.
33.00	Spur, slopes SE.; desc. along E. slope.
39.98	The cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 16x10x8 ins., dimly mkd. with 5 notches on the S. edge and 1 notch on the N. edge and firmly set in a mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T40N  R48E R49E  S 1   S 6  S 12   S 7 </div>
	1970
	bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 13° 00' E., bet. secs. 1 and 6.
	Over mountainous land, through scattered sagebrush and native grass; desc. 30 ft. over N. slope.
3.60	Wash, 10 lks. wide, 1 ft. deep, drains SE.
4.20	Trail road, bears NW. and SE.; asc. 330 ft. over S. slope.
44.20	Spur, slopes E.; desc. 80 ft. over N. slope.
52.79	Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T40N  R48E R49E  ¼  S 1   S 6 </div>
	1970