

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 40 N., R. 48 E.

CHAINS

- N. 16° 32' E., bet. secs. 1 and 2.
- Over mountainous land, through scattered sagebrush and native grass; desc. 10 ft. along E. slope.
- 5.40 Wash, 10 lks. wide, 1 ft. deep, drains SSE.; asc. 640 ft. over SW. slope.
- 32.00 Ridge, bears NNW. and SSE.; desc. 70 ft. along rolling E. slope.
- 55.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T40N R48E
 $\frac{1}{4}$
S 2 | S 1
1970
- raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- From this corner a spring, bears S. 85° E., 15.35 chs. dist.
- Desc. 290 ft. along E. slope.
- 64.40 Ravine, drains E.; asc. 50 ft. along E. slope.
- 89.50 Spur, slopes E.; desc. 290 ft. over NE. slope.
- 110.50 Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. 290 ft. over S. slope.
- 136.80 Ridge, with trail road along top, bears ENE. and WSW.; desc. 260 ft. over N. slope.
- 149.40 Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. 160 ft. over rolling SE. slope.
- 176.20 Spur, slopes E.; desc. 70 ft. over N. slope.
- 187.30 Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 290 ft. over SW. slope.
- 199.39 Intersect the Eighth Standard Parallel North.
- Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., on solid rock over a cross (X) and in a mound of stone to cap, 5 ft. base, with brass cap mkd.