

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 40 N., R. 48 E.

CHAINS	
150.90	Head of ravine, drains E.; asc. 130 ft. along E. slope.
160.70	Spur, slopes SSE.; asc. along E. slope.
173.20	Spur, slopes E.; desc. 180 ft. over N. slope.
180.80	Ravine, drains E.; asc. 140 ft. over S. slope.
188.00	Spur, slopes E.; desc. 240 ft. over N. slope.
195.70	Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. 30 ft. over S. slope.
199.04	Intersect the Eighth Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.
	<p style="text-align: center;">T41N R48E $\frac{S}{4} \frac{36}{S} \frac{3}{3}$ T40N R48E C C</p>
	1970
	From this corner the standard ¼ sec. cor. of sec. 36, T. 41 N., R. 48 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Eighth Standard Parallel North, through R. 48 E., resurveyed concurrently under this same group, bears N. 89° 52' E., 16.43 chs. dist.
	Point for the N. ¼ sec. cor. of sec. 3, is on the Eighth Standard Parallel North and at midpoint on the N. bdy. of sec. 3.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">$\frac{1}{4} \frac{S}{S} \frac{3}{3}$ T40N R48E</p>
	1970
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.