

SURVEY OF A PORTION OF THE THIRD STANDARD PARALLEL NORTH,
THROUGH RANGE 70 EAST

CHAINS	
	Asc. 530 ft. over steep broken E. slope.
80.00	Point for the standard cor. of secs. 33 and 34. Set an iron post, 28 ins. long, 2½ ins. diam., on bedrock over a cross (X) and in a mound of stone to cap, 4 ft. base, with brass cap mkd. <div style="text-align: center;"> S C T16N R70E <u>S 33 S 34</u> 1969 </div>
	Land, rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush and greasewood.
<p>SURVEY OF CERTAIN SUBDIVISIONAL LINES OF T. 16 N., R. 70 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	From the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp. N. 0° 03' E., bet. secs. 34 and 35. Over rolling mountainous land, through scattered undergrowth.
1.50	Wash, 15 lks. wide, 2 ft. deep, drains NE.; asc. 30 ft. over S. slope.
10.50	Spur, slopes E.; desc. 90 ft. over N. slope.
17.00	Wash, 15 lks. wide, 2 ft. deep, drains E.; trail road in wash, bears E. and W.; asc. 120 ft. over S. slope.
28.90	Spur, slopes SE.; desc. 190 ft. over NE. slope.
40.00	Point for the ¼ sec. cor. of secs. 34 and 35. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd. <div style="text-align: center;"> T16N R70E ¼ S 34 S 35 1969 </div>
	Desc. 220 ft. over NE. slope.
49.00	Ravine with creek in bottom, 5 lks. wide, 6 ins. deep, flows NE.