

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 35 N., R. 42 E.

CHAINS

T35N R42E

$$\begin{array}{c} \frac{1}{4} \\ S \ 6 \ | \ S \ 5 \end{array}$$

1969

reset the remains of the wooden post alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.

N. 0° 45' E., beginning new measurement.

Over gently rolling land, through greasewood.

26.90 Base of rolling land, bears NE. and SW.; asc. 40 ft. over a SW. slope.

38.90 Intersect the Seventh Standard Parallel North.

Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R42E

$$\begin{array}{c} S \ 31 \\ \hline S \ 6 \ | \ S \ 5 \\ CC \end{array}$$

T35N R42E

1969

raise a mound of stone, 2½ ft. base, 2 ft. high, S. of the cor.

From this corner, the standard ¼ sec. cor. of sec. 31, T. 36 N., R. 42 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears S. 89° 49' W., 18.10 chs. dist.

From this same corner, the standard cor. of secs. 31 and 32, T. 36 N., R. 42 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears N. 89° 49' E., 21.99 chs. dist.

Point for the N. ¼ sec. cor. of sec. 6 is on the Seventh Standard Parallel North and at proportionate distance on the N. bdy. of sec. 6.