Survey, F	Portion	of	the	Subdivisional	Lines,	т.	5	Ν.,	R.	42	Ε.
-----------	---------	----	-----	---------------	--------	----	---	-----	----	----	----

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the corner.

Descend 130 ft. over rolling W. slope.

40.25 Dirt road, 15 1ks. wide, bears N. and S.

80.10 Dirt road, 15 lks. wide, bears N. 15° E. and irregularly S.

80.46 Intersect the W. bdy. of the Tp.

Point for the closing cor. of secs. 7 and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground with brass cap mkd.

Set a steel fence post, 5 ft. long, E. of the corner

From this point, the cor. of secs. 12 and 13 only, T. 5 N., R. 41 E., bears N. 0° 08' E., 11.04 chs. dist., hereinbefore described.

Land, rolling desert. Soil, sandy and gravelly.

No timber; vegetation consists of sagebrush, greasewood, and rabbitbrush.

To complete the survey of sec. 18, I return to the $\frac{1}{4}$ sec. cor. of sec. 13 only, on the E. bdy. of T. 5 N., R. 41 E. and run

S. 0° 08' W., on the W. bdy. of sec. 18.

Point for the ½ sec. cor. of sec. 18 only, at midpoint latitudinally on the W. bdy. of sec. 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

Set a steel fence post, 5 ft. long, E. of the corner.

From the cor. of secs. 7 and 18 only.

N. 0° 03' W., on the E. bdy. of sec. 7.