Survey	Portion	of	the	Subdivisional	Lines.	T.	5	Ν	R.	42	Ε.
DULVEY	TOTETOIL	$\circ$	CIIC	Dubaryrbronar			_				

S	Survey, Portion of the Subdivisional Lines, T. 5 N., R. 42 E.
CHAINS	Descend 155 ft. over rolling W. slope.
40.15	Dirt road, 15 1ks. wide, bears N. and S.
79.80	Dirt road, 15 lks. wide, bears N. and S.
79.95	Intersect the W. bdy. of the Tp.
	Point for the closing cor. of secs. 6 and 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
	Raise a mound of stone, 4 ft. base, 3 ft. high, E. of the corner.
	From this point, the cor. of secs. 1 and 12 only, T. 5 N., R. 41 E., bears N. 0° 14' E., 11.31 chs. dist., hereinbefore described.
	Land, E. 12 chs. rolling foothills, W. 68 chs. rolling desert. Soil, rocky and sandy. No timber; vegetation consists of sagebrush, greasewood, and rabbitbrush.
	To complete the survey of sec. 7, I return to the ½ sec. cor. of sec. 12 only, on the E. bdy. of T. 5 N., R. 41 E. and run
	S. 0° 25' W., on the W. bdy. of sec. 7.
11.20	Point for the ½ sec. cor. of sec. 7 only, at midpoint latitudinally on the W. bdy. of sec. 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	T 5 N R 42 E ½ S 7 1970
	Set a steel fence post, 5 ft. long, E. of the corner
	From the cor. of secs. 6 and 7 only.
	N. 0° 03' W., on the E. bdy. of sec. 6.
	Descend 55 ft. over broken NW. slope, through scattering sagebrush.
4.90	Dirt road, 15 lks. wide, bears E. and W., in a dry wash, drains W.; asc. 20 ft. over broken SW. slope.
7.29	Intersect line 4-1 of Utica, M. S. No. 3481.