

Completion Survey of the Subdivisional Lines of
Sections 30, 31, and 32, T. 6 N., R. 42 E.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to bedrock, and in a mound of stone, 4½ ft. base, to top, with brass cap mkd.
	<p style="text-align: center;"> <u>¼ S 32</u> T 6 N R 42 E 1970 </p>
	Descend 305 ft. over steep rocky W. slope.
56.40	Dry wash, drains NW.; desc. 65 ft. over broken W. slope.
80.08	The cor. of secs. 29, 30, 31, and 32.
	Land, mountainous. Soil, rocky and sandy. No timber; vegetation consists of sagebrush, greasewood, and rabbitbrush.
	West, on a sectional correction line, bet. secs. 30 and 31.
	Descend 130 ft. over rolling W. slope, through scattering sagebrush.
7.30	Dirt road, 15 lks. wide, bears N. and S.
42.26	Point for the ¼ sec. cor. of sec. 31 only.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, and in a mound of stone, 1½ ft. base, to top, with brass cap mkd.
	<p style="text-align: center;"> <u>¼ S 31</u> T 6 N R 42 E 1970 </p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.
	Descend over nearly level W. slope.
42.96	Point for the ¼ sec. cor. of sec. 30 only.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, and in a mound of stone, 1½ ft. base, to top, with brass cap mkd.
	<p style="text-align: center;"> T 6 N R 42 E <u>¼ S 30</u> 1970 </p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the corner.
	Descend 105 ft. over W. slope.
82.26	Intersect the W. bdy. of the township.
	Point for the closing corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.