

## DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 15 S., R. 68 E.

CHAINS

bury the original cornerstone alongside the iron post and raise a mound of stone, 5 ft. base, 3 ft. high, N. of cor.

S. 89° 52' W., beginning new measurement.

Over broken W. slope; desc. 90 ft. to the sec. cor.

13.60 Graded road, bears NE. and SW.

40.43 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15S R68E

S 31 | S 32

S 6 | S 5

T16S

1970

raise a mound of stone, 5 ft. base, 3 ft. high, W. of cor.

S. 89° 52' W., bet. secs. 6 and 31.

Over rolling hills, through light budsage and shadscale; desc. 50 ft. to the ¼ sec. cor.

14.20 Gulch, drains SW.

40.43 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15S R68E

¼ S 31

S 6

T16S

1970

raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

Descend 80 ft. over rolling hills.

81.16 The cor. of Tps. 15 and 16 S., Rs. 67 and 68 E., monument-  
ed with a limestone, 8x6x4 ins., mkd. with 6 grooves and  
W on the W. face, 6 grooves and N on the N face, 6  
grooves on the E. face and 6 grooves on the S. face,  
firmly set in a small mound of stone.