DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

T. 5 N., R. 60 E. CHAINS Point for the N. ½ sec. cor. of sec. 1, on the S. bdy. of sec. 36, T. 6 N., R. 60 E., and at midpoint on the N. bdy. of sec. 1. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. **T6N R60E** ½ S 1 T5N R60E 1970 set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post. From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 6 N., R. 60 E., hereinbefore described, bears N. 89° 48' E., 13.91 chs. dist. From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 4 N., R. 60 E., concurrently resurveyed under this same Group. N. 0° 33' E., bet. secs. 34 and 35. Over nearly level land, through sagebrush and shadscale. 39.65 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T5N R60E 1970 set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post. 79.30 The cor. of secs. 26, 27, 34 and 35, monumented with a cedar post, 3x3x20 ins., loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.