

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 5 N., R. 60 E.

CHAINS

T5N R60E

$$S \ 3 \frac{1}{4} \ S \ 2$$

1970

reset the cedar post and set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.

N. 0° 33' W., beginning new measurement.

Over nearly level land.

40.85 Intersect the First Standard Parallel North on the S. bdy. of sec. 34, T. 6 N., R. 60 E.

The closing cor. of secs. 2 and 3, monumented with a cedar post, 2x2x26 ins., loosely set in a mound of earth and plainly scribed.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T6N R60E

S 34

$$S \ 3 \ S \ 2$$

CC

T5N R60E

1970

reset the cedar post and set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.

From this corner, the standard cor. of secs. 34 and 35, T. 6 N., R. 60 E., hereinbefore described, bears S. 89° 36' E., 13.34 chs. dist.

Point for the N. ¼ sec. cor. of sec. 2, on the S. bdy. of sec. 35, T. 6 N., R. 60 E., and at midpoint on the N. bdy. of sec. 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T6N R60E

$$\frac{1}{4} \ S \ 2$$

T5N R60E

1970

set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.

From this corner, the standard ¼ sec. cor. of sec. 35, T. 6 N., R. 60 E., hereinbefore described bears S. 89° 39' E., 13.25 chs. dist.