DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES T. 5 N., R. 60 E.

		1. 5 N., R. 60 E.
	CHAINS	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 4 N., R. 60 E., concurrently resurveyed under this
		N. 0° 17' E., bet. secs. 33 and 34.
		Over nearly level land, through sagebrush and shadscale.
	39.30	Point for the ½ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T5N R60E
		S 33 S 34
		1970
		set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
	78.60	The cor. of secs. 27, 28, 33 and 34, monumented with a cedar post, 2x2x30 ins., loosely set in a mound of earth and plainly scribed.
		At the corner point
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T5N R60E S 28 S 27 S 33 S 34
		1970
		reset the cedar post and set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
		From the cor. of secs. 26, 27, 34 and 35.
		N. 89° 51' W., bet. secs. 27 and 34.
		Over nearly level land, through sagebrush.
	40.61	The $\frac{1}{2}$ sec. cor. of secs. 27 and 34, monumented with a cedar post, $2x2x20$ ins., loosely set in a mound of earth.
		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
1		