

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 5 N., R. 60 E.

CHAINS

T5N R60E

$$\begin{array}{c} \frac{1}{2} \\ S \ 4 \ | \ S \ 3 \end{array}$$

1970

set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post.

81.20 Intersect the First Standard Parallel North on the S. bdy. of sec. 33, T. 6 N., R. 60 E.

The closing cor. of secs. 3 and 4, monumented with a cedar post, 3x3x26 ins., loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T6N R60E

$$\begin{array}{c} S \ 33 \\ \hline S \ 4 \ | \ S \ 3 \end{array}$$

CC

T5N R60E

1970

reset the cedar post and set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post.

From this corner, the standard cor. of secs. 33 and 34, T. 6 N., R. 60 E., hereinbefore described, bears S.  $89^{\circ} 56'$  E., 12.99 chs. dist.

Point for the N.  $\frac{1}{2}$  secs. cor. of sec. 3, on the S. bdy. of sec. 34, T. 6 N., R. 60 E., and at midpoint on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T6N R60E

$$\begin{array}{c} \frac{1}{2} \ S \ 3 \\ \hline T5N \ R60E \end{array}$$

1970

set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post.

From this corner, the standard  $\frac{1}{2}$  sec. cor. of sec. 34, T. 6 N., R. 60 E., hereinbefore described, bears S.  $89^{\circ} 56'$  E., 13.15 chs. dist.