

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 5 N., R. 61 E.

CHAINS

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T5N R61E

$\frac{1}{4}$
S 4 | S 3

1970

set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.

44.40 Graded gravel road, bears SSE. and NNW.

79.92 Intersect the S. bdy. of sec. 33, T. 6 N., R. 61 E.

Point for the closing cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T6N R61E

S 33
S 4 | S 3

C | C

T5N R61E

1970

set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.

From this corner, the standard cor. of secs. 33 and 34, T. 6 N., R. 61 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 6 N., R. 61 E., resurveyed concurrently under this same Group, bears N. $89^{\circ} 59' E.$, 15.58 chs. dist.

From this same corner, the original closing cor. of secs. 3 and 4, monumented with the remains of a cedar post, wired to a steel fence post, bears N. $0^{\circ} 17' E.$, 0.19 chs. dist.

At the corner point

Set a copper-coated steel stake, 18 ins. long, $\frac{1}{2}$ in. diam., 14 ins. in the ground, with brass cap mkd. AM 1970.

reset the remains of the cedar post and the steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the steel stake.