

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 5 N., R. 61 E.

CHAINS  
78.34

The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the field notes of T. 5 N., R. 60 E., resurveyed concurrently under this same Group.

From the cor. of secs. 5, 6, 7 and 8.

N.  $1^{\circ} 17'$  E., bet. secs. 5 and 6.

Over nearly level land, through shadscale, budsage and sagebrush.

5.60 Wash, 20 lks. wide, 2 ft. deep, drains NW.

40.33 Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T5N R61E  
 $\frac{1}{4}$   
S 6 | S 5  
1970

set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post.

80.82 Intersect the First Standard Parallel North on the S. bdy. of sec. 31, T. 6 N., R. 61 E.

The closing cor. of secs. 5 and 6, monumented with an iron pipe,  $2\frac{1}{2}$  ins. diam., showing 10 ins. above the ground, with the galvanized steel cap mkd. secs. 5 and 6 only. This private survey pipe is accepted as the best remaining evidence of the position of the original corner and I remark the cap as follows:

T6N R61E  
S 31  
S 6 | S 5  
C | C  
T5N R61E  
1970

set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post.

From this corner, the standard cor. of secs. 31 and 32, T. 6 N., R. 61 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the field notes of T. 6 N., R. 61 E., resurveyed concurrently under this same Group, bears N.  $89^{\circ} 45'$  E., 14.44 chs. dist.

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 5, is on the S. bdy. of sec. 32, T. 6 N., R. 61 E., and at midpoint on the N. bdy. of sec. 5.