

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL NORTH,
THROUGH 61 E.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T6N R61E R62E <u>S 36 S 31</u></p> <p style="text-align: center;">1970</p> <p>set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post and raise a mound of stone, 3½ ft. base, 2 ft. high N. of cor.</p> <p>From this corner, the original standard cor. of secs. 31 and 32, T. 6 N., R. 62 E., now an AM, monumented with a copper-coated steel stake, as described in the field notes of the concurrent surveys in T. 6 N., R. 62 E., executed under this same group, bears S. 89° 54' E., 79.86 chs. dist.</p> <p>N. 89° 54' W., along the S. bdy. of sec. 36.</p> <p>Over nearly level land, through sagebrush and whitesage.</p>
17.47	The closing cor. of Tps. 5 N., Rs. 61 and 62 E., monumented with the remains of a cedar post, wired to a steel fence post, bears NORTH, 0.16 chs. dist.
39.93	<p>The standard ¼ sec. cor. of sec. 36, monumented with a limestone, 4x6x7 ins., firmly set and plainly mkd. ¼ on the N. face, with a steel fence post set alongside. The geographic position of this monument was determined under Group No. 389.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd..</p> <p style="text-align: center;">S C T6N R61E <u>¼ S 36</u></p> <p style="text-align: center;">1970</p> <p>bury the cornerstone and reset the steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 52' W., beginning new measurement.</p> <p>Over nearly level land.</p>
4.70	Wash, 40 lks. wide, 2 ft. deep, drains WSW.
40.08	The standard cor. of secs. 35 and 36, monumented with a cedar post, 2x2x20 ins., wired to a steel fence post and dimly scribed.