

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL NORTH,
THROUGH R. 61 E.

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T6N R61E <u>½ S 32</u></p> <p style="text-align: center;">1970</p> <p>reset the cedar post and set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.</p> <hr/> <p>N. 89° 19' W., beginning new measurement.</p> <p>Over nearly level land.</p>
16.03	<p>The N. ¼ sec. cor. of sec. 5, T. 5 N., R. 61 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 5 N., R. 61 E., executed under this same Group.</p>
40.88	<p>The standard cor. of secs. 31 and 32, monumented with an iron pipe, 2½ ins. diam., showing 10 ins. above the ground, with the galvanized steel cap mkd. secs. 31 and 32 only. This private survey pipe is accepted as the best remaining evidence of the position of the original corner and I remark the cap as follows:</p> <p style="text-align: center;">S C T6N R61E <u>S 31 S 32</u></p> <p style="text-align: center;">1970</p> <p>set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.</p> <hr/> <p>S. 89° 45' W., along the S. bdy. of sec. 31.</p> <p>Over nearly level land, through sagebrush, shadscale and greasewood.</p>
12.00	<p>Trail road, bears SSE. and NNW.</p>
14.44	<p>The closing cor. of secs. 5 and 6, T. 5 N., R. 61 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 5 N., R. 61 E., executed under this same Group.</p>
22.00	<p>Trail road, bears NE. and SW.</p>
22.20	<p>Fence, bears NE. and SW.</p>
35.70	<p>Trail road, bears NNE. and SSW.</p>