

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL NORTH,  
THROUGH R. 61 E.

CHAINS  
39.85

Point for the standard  $\frac{1}{4}$  sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

S C  
T6N R61E  
 $\frac{1}{4}$  S 31

1970

set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post.

41.40

East edge of Hay Meadow Reservoir, bears NNE. and SSW.; thence across reservoir.

55.48

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 6, T. 5 N., R. 61 E., as described in the field notes of the concurrent resurvey of T. 5 N., R. 61 E., executed under this same Group.

70.70

West edge of Hay Meadow Reservoir, bears NE. and SW.; thence across nearly level land.

79.70

The standard cor. of Tps. 6 N., Rs. 60 and 61 E., monumented with an iron pipe,  $2\frac{1}{2}$  ins. diam., showing 10 ins. above the ground, with the galvanized steel cap mkd. secs. 31 and 36 only. This private survey pipe is accepted as the best remaining evidence of the position of the original corner and I remark the cap as follows:

S C  
T6N  
R60E R61E  
S 36 | S 31

1970

set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post.

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF  
T. 6 N., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of the Survey Executed by E. B. Monroe,  
U. S. Deputy Surveyor, in 1871.

These corners were originally established to function for Rs. 61 and 62 E. They will now function for R. 61 E. only.

From the standard cor. of Tps. 6 N., Rs. 61 and 62 E.  
N.  $0^{\circ} 14'$  E., along the E. bdy. of sec. 36.

Over nearly level land, through budsage, shadscale and sagebrush.

2.30

Wash, 40 lks. wide, 3 ft. deep, drains WNW.