CHAINS	
	DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF T. 6 N., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by E. B. Monroe, U. S. Deputy Surveyor, in 1871.
	From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.
	N. 0° 44' E., bet. secs. 35 and 36.
	Over nearly level land, through whitesage and sagebrush.
9 .2 0	Trail road, bears ENE. and WSW.
40.46	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T6N R61E
	S 35 S 36
	. 1970 .
	set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
49.70	Trail road, bears NNE. and SSW.
80.92	The cor. of secs. 25, 26, 35 and 36, monumented with a cedar post, 2x2x26 ins., loosely set in a mound of earth and dimly scribed.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T6N R61E <u>S 26 S 25</u> S 35 S 36
	1970 reset the cedar post and set a steel fence post, $5\frac{1}{2}$ ft.
	long, 2½ ft. in the ground, alongside the iron post.
	From the cor. of secs. 25 and 36 on the E. bdy. of the Tp
	N. 89° 21' W., bet. secs. 25 and 36.
	Over nearly level land, through sagebrush and shadscale.

4