

INDEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL NORTH,
THROUGH R. 62 E.

CHAINS	
	<p>INDEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL NORTH, THROUGH R. 62 E.</p> <hr/> <p>This Independent Resurvey supersedes the survey executed by E. B. Monroe and A. G. Bateman, U. S. Deputy Surveyors in 1872. A diligent search was made for the original corners and those found are described in the following notes.</p> <hr/> <p>The standard cor. of Tps. 6 N., Rs. 62 and 63 E., monumented with a blue limestone, 8x10x14 ins., firmly set and plainly mkd. with 6 notches on the E. and W. faces and with a steel fence post set alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T6N R62E R63E <u>S 36 S 31</u></p> <p style="text-align: center;">1970</p> <p>bury the cornerstone and reset the steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.</p> <p>N. 89° 42' W., along the S. bdy. of sec. 36.</p> <p>Over mountainous land, through sagebrush and scattered pinon and juniper; asc. 80 ft. over a SE. slope.</p> <p>16.30 Ravine, drains SE.; asc. 70 ft. over a N. slope.</p> <p>24.50 Saddle, bears SE. and NW.; desc. 20 ft. over a S. slope.</p> <p>40.00 Point for the standard ¼ sec. cor. of sec. 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to the cap, 3½ ft. base, with brass cap mkd.</p> <p style="text-align: center;">SC T6N R62E <u>¼ S 36</u></p> <p style="text-align: center;">1970</p> <p>40.03 The original standard ¼ sec. cor. of sec. 36, monumented with a blue limestone, 8x8x12 ins., firmly set and dimly mkd. ¼ on the N. face, bears NORTH, 0.38 chs. dist. I destroy this monument.</p> <p>41.20 Wash, 20 lks. wide, 3 ft. deep, drains SE.; asc. 190 ft. over a NE. slope.</p>