## INDEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL NORTH, THROUGH R. 62 E.

CHAINS

77.52

The standard cor. of Tps. 6 N., Rs. 61 and 62 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the field notes of T. 6 N., R. 61 E., resurveyed concurrently under this same group.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF T. 7 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of the Survey Executed by E. B. Monroe and A. G. Bateman, U. S. Deputy Surveyors, in 1871.

These corners were originally established to function for Tps. 6 and 7 N. They will now function for T. 7 N. only.

The cor. of secs. 33 and 34, T. 7 N., R. 62 E., monumented with a limestone,  $8 \times 10 \times 12$  ins., firmly set in a mound of stone and plainly mkd. with 3 notches on the E. and W. edges.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., over a cross (x) on bedrock and in a mound of stone to the cap,  $4\frac{1}{2}$  ft. base, with brass cap mkd.

T7N R62E S33 S 34 S 3 T6N

1970

bury the cornerstone alongside the iron post.

S. 89° 56' W., along the S. bdy. of sec. 33.

Over mountainous land, through shadscale, budsage and scattered juniper; desc. 120 ft. over a W. slope.

4.17 The closing cor. of secs. 3 and 4, T. 6 N., R. 62 E., hereinafter described.

Desc. 80 ft. over a W. slope.

9.00 Ravine, drains WSW.; desc. 10 ft. over a S. slope.

16.00 Slope changes; desc. 140 ft. over a W. slope.

40.08 The ½ sec. cor. of sec. 33, T. 7 N., R. 62 E., monumented with a limestone, 6x8x8 ins., firmly set in a mound of earth and dimly mkd. ½ on the N. face, with a steel fence post set alongside.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.