

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF  
T. 6 N., R. 62 E.

CHAINS	
	<p>set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy gravel. Undergrowth, shadscale and budsage.</p> <hr/> <p>N. 0° 01' W., bet. secs. 3 and 4.</p> <p>Over rolling land, through medium undergrowth; asc. 40 ft. over a W. slope.</p>
19.99	<p>A copper-coated steel stake, ½ in. diam., showing 6 ins. above the ground, with brass cap mkd. NEVADA HWY. DEPT. NYJ 005 and a fence post, 5½ ft. long, 2½ ft. in the ground, bears WEST, 0.17 chs. dist.</p> <p>Slope changes; desc. 20 ft. over a W. slope.</p>
24.20	<p>Trail road, bears ESE. and WNW.; desc. 30 ft. over a W. slope.</p>
30.50	<p>Wash, 30 lks. wide, 4 ft. deep, drains NW.; desc. 40 ft. over a W. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) on bedrock and in a mound of stone to the cap, 4 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T6N R62E ¼ S 4   S 3  1970</p> <p>Asc. 30 ft. over a W. slope.</p>
57.20	<p>Ravine, drains W.; asc. 80 ft. over a W. slope.</p>
65.00	<p>Spur, slopes W.; desc. 140 ft. over a W. slope.</p>
80.16	<p>Intersect the S. bdy. of sec. 33, T. 7 N., R. 62 E.</p> <p>Point for the closing cor. of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to the cap, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T7N R62E S 33 S 4   S 3 C C T6N R62E  1970</p>