1

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF

	- $ -$
CHAINS	
	N. 0° 02' W., bet. secs. 4 and 5.
	Over gently rolling land, through medium undergrowth; desc. 50 ft. over a W. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T6N R62E
	z s 5 s 4
	1970
	set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
	Desc. 50 ft. over a W. slope.
75.30	Wash, 20 lks. wide, 5 ft. deep, drains W.
80.84	Intersect the S. bdy. of sec. 32, T. 7 N., R. 62 E.
	Point for the closing cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T7N R62E <u>S 32</u> <u>S 5 S 4</u> <u>C C</u> T6N R62E
	1970
	set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
	From this corner, the cor. of secs. 32 and 33, T. 7 N., R. 62 E., heretofore described, bears S. 89° 19' E., 4.25 chs. dist.
	Land, gently rolling. Soil, sandy gravel. Undergrowth, shadscale and budsage.
	Point for the N. ½ sec. cor. of sec. 4, is on the S. bdy. of sec. 33, T. 7 N., R. 62 E., and at midpoint on the N. bdy. of sec. 4.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to the cap, 4 ft. base, with brass cap mkd.
	· · · · · · · · · · · · · · · · · · ·