SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 6 N., R. 62 E. CHAINS Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{T6N R62E} \\ \frac{1}{4} & \frac{\text{S}}{\text{S}} & \frac{7}{18} \end{array}$ 1970 set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post. From this corner, a drill hole with a capped 8 in. casing, bears N. 37° 09' W., 20.67 chs. dist. 76.40 Intersect the E. bdy. of sec. 13, T. 6 N., R. 61 E. Point for the closing cor. of secs. 7 and 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T6N R61E R62E S13 S 7 C S18 C 1970 set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post. From this corner, the cor. of secs. 12 and 13, T. 6 N., R. 61 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 6 N., R. 61 E., bears N. 0° 06' E., 2.41 chs. dist. Land, nearly level. Soil, sandy gravel. Undergrowth, shadscale, greasewood and sagebrush. Point for the W. $\frac{1}{2}$ sec. cor. of sec. 18, is on the E. bdy. of sec. 13, T. 6 N., R. 61 E., and at midpoint on the W. bdy. of sec. 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T6N R61E R62E 1 5 18 1970 set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.

249

GPO 845-166