## SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 6 N., R. 62 E.

<del>,</del>	T. 6 N., R. 62 E.
CHAINS	
	From this corner, the E. ½ sec. cor. of sec. 1, T. 6 N., R. 61 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 6 N., R. 61 E., bears N. 0° 37' E., 2.64 chs. dist.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 03' W., bet. secs. 5 and 6.
	Over nearly level land, through medium undergrowth.
40.00	Point for the 1/2 sec. cor. of secs. 5 and 6.
·	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
·	T6N R62E
	S 6 S 5
	1970
	set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
48.20	Wash, 20 lks. wide, 2 ft. deep, drains WNW.
78.90	Graded gravel road, curving ENE. and WNW.
81.84	Intersect the S. bdy. of sec. 31, T. 7 N., R. 62 E.
	Point for the closing cor. of secs. 5 and 6.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a fence, bearing E. and W., with brass cap mkd.
	T7N R62E
	S 31 S 6   S 5
	C C T6N R62E
	1970
	From this corner, the cor. of secs. 31 and 32, T. 7 N., R. 62 E., heretofore described, bears S. 89° 19' E., 4.19 chs. dist.
	Land, nearly level. Soil, sandy gravel. Undergrowth, shadscale, greasewood and sagebrush.
	Point for the N. ½ sec. cor. of sec. 5, is on the S. bdy. of sec. 32, T. 7 N., R. 62 E., and at midpoint on the N. bdy. of sec. 5.