

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF
T. 24 N., R. 18 E.

CHAINS		
	<p>N. 89° 46' W., beginning new measurement.</p> <p>Over gently rolling land, through scattered juniper and sagebrush; over a gentle SW. slope.</p> <p>5.50 The S. $\frac{1}{4}$ sec. cor. of sec. 32, T. 25 N., R. 18 E., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.</p> <p>Desc. 120 ft. over a SW. slope.</p> <p>39.20 The cor. of secs. 5 and 6, monumented with a granite stone, 22x10x8 ins., plainly mkd. with 5 grooves on the E. face and 1 groove on the W. face and firmly set in a collar of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to cap, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R18E</p> <p>S 32</p> <hr/> <p>S 6 S 5</p> <p>T24N R18E</p> <p>1970</p> </div> <p>deposit the corner stone alongside the iron post.</p>	
	<p>N. 89° 56' W., along the N. bdy. of sec. 6.</p> <p>Over nearly level land, through scattered juniper and sagebrush.</p> <p>5.25 The closing cor. of Tps. 24 and 25 N., R. 18 E., monumented with a granite stone, 12x10x10 ins., plainly mkd. with 5 grooves on the E. face and 6 grooves on both the N. and S. faces, NEV on the E. face, CAL on the W. face and firmly set in a collar of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N</p> <p>R18E</p> <p>S 32</p> <hr/> <p>S 6 S 6 CC</p> <p>T24N</p> <p>R18E</p> <p>1970</p> </div> <p>deposit the corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p>	