DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 24 N., R. 18 E.

 	T. 24 N., R. 18 E.	
CHAINS		!
	T24N R18E	
	<u>S 7   S 8</u> S 18   S 17	
	1970	
• :	deposit the post fragments alongside the iron post and	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of	
	cor.	
	From the cor. of secs. 8, 9, 16 and 17.	
· · · · · · · · · · · · · · · · · · ·	N. 87° 59' W., bet. secs. 8 and 17.	
	Over nearly level land, through medium dense sagebrush.	
41.03	The ½ sec. cor. of secs. 8 and 17, the position for which is determined longitudinally by a fence bearing N. and S. and latitudinally on line bet. the cor. of secs. 8, 9, 16 and 17, and the cor. of secs. 7, 8, 17 and 18.	
·	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
4	T24N R18E	
	S 8 4 S 17	
	1970	
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.	
·	N. 87° 59' W., beginning new measurement.	
	Over nearly level land, through medium dense sagebrush.	
32.00	Dim track road, bears SE. and NW.	
38.10	Wash, 30 lks. wide, 2 ft. deep, drains N.	
38.52	The cor. of secs. 7, 8, 17 and 18.	
 : ** 	N. 85° 50' W., bet. secs. 7 and 18.	
·	Over rolling land, through scattered sagebrush.	
7.03	The closing cor. of secs. 7 and 18, on the Nevada-California State Line, monumented with the fragments of a pine post centered in a mound of well imbedded stone, 3½ ft. base, 1 ft. high.	
	At the corner point	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to rock and in a collar of stone, with brass cap mkd.	
	·	