

DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH BOUNDARY AND  
REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS, T. 33 N., R. 58 E.

CHAINS	<p>Beginning at the SE. cor. of T. 33 N., R. 58 E., monument- ed with a granite stone, 18x16x8 ins., mkd. with 6 grooves on the N. face and 6 grooves on the W. face, firmly set, protruding 6 ins. above ground, from which the 1917 bearing trees:</p> <p>An aspen, 10 ins. diam., bears N. 48 3/4° E., 17 lks. dist., mkd. T33N R59E S31 BT.</p> <p>An aspen, 10 ins. diam., bears N. 34½° W., 24 lks. dist., mkd. T33N R58E S36 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div><div>T33N R58E S 36</div><div>T33N R59E S 31</div></div> <p>1970</p> <p>bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, NW. of cor.</p> <p>N. 89° 47' W., along the S. bdy. of sec. 36.</p> <p>Over mountainous terrain, through heavy timber and light brush; desc. 200 ft. over W. slope.</p> <p>8.56 The NE. cor. of T. 32 N., R. 58 E., monumented with an iron post, 3 ins. diam., in a mound of stone, 3 ft. base to top, with mound of stone, 3 ft. base, 2 ft. high, S. of cor., with brass cap mkd.</p> <div><div>T33N R58E S 36</div><div>S 1   S 31 T33N R58E   R59E T32N</div></div> <p>1916</p> <p>Desc. 90 ft. over W. slope.</p> <p>14.10 Conrad Creek, 2 lks. wide, course NNW.; desc. 100 ft. over W. slope.</p> <p>20.40 Draw, drains NNW.; asc. 20 ft. along a N. slope.</p> <p>40.06 The ¼ sec. cor. of sec. 36, monumented with a granite stone, 18x6x6 ins., mkd. ¼ on the N. face, firmly set in a small mound of stone.</p> <p>At the corner point</p>
--------	--