

DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH BOUNDARY AND  
REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS, T. 33 N., R. 58 E.

CHAINS	
	<p>The cor. of secs. 31 and 32, monumented with a granite stone, 27x12x6 ins., mkd. with 1 groove on the W. face and 5 grooves on the E. face, firmly set, protruding 13 ins. above ground, with mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R58E  <u>S 31   S 32</u>  T32N R58E  S 5</p> <p>1970</p> </div> <p>deposit the original corner stone alongside the iron post and rebuild the mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p>
	<p>The ¼ sec. cor. of sec. 31, monumented with a granite stone, 28x16x5 ins., mkd. ¼ on the N. face, firmly set, protruding 16 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R58E  <u>¼ S 31</u></p> <p>1970</p> </div> <p>deposit the original corner stone alongside the iron post and rebuild the mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p>
	<p>The cor. of Tps. 33 N., Rs. 57 and 58 E., monumented with a granite stone, 30x12x5 ins., mkd. with 6 grooves and R57E on the W. face, 6 grooves and T33N on the N. face, and 6 grooves and T58E on the E. face, firmly set, protruding 16 ins. above ground, with a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N  R57E R58E  <u>S 36   S 31</u>  T32N R58E  S 6</p> <p>1970</p> </div>