

DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH BOUNDARY AND
REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS, T. 33 N., R. 58 E.

CHAINS

deposit the original corner stone alongside the iron post and rebuild the mound of stone, 4 ft. base, 3 ft. high, N. of cor.

This corner is located 40 lks. S. of a graded road, bears ENE. and WSW., leading to the Ruby Dome Ranch.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY AND
REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,
T. 33 N., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
Henry Thurtell, U. S. Compassman, in 1903,
and a Portion of the Resurvey Executed by
Thomas A. Haigh, U. S. Surveyor, in 1917.

The $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a granite stone, 18x10x3 ins., mkd. $\frac{1}{4}$ on the W. face, firmly set, protruding 8 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T33N	
R58E	
$\frac{1}{4}$	
S 36	

1970

deposit the original corner stone alongside the iron post and rebuild the mound of stone, 4 ft. base, 3 ft. high, W. of cor.

The cor. of secs. 24 and 25, monumented with a granite stone, 18x12x4 ins., mkd. with 4 grooves on the N. face, and 2 grooves on the S. face, firmly set in a mound of stone, on N. side of large rock outcrop.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 6 ft. base to top, with brass cap mkd.

T33N	T33N
R58E	R59E
$\frac{S}{S}$ 24	
S 25	S 19

1970

deposit the original corner stone alongside the iron post.