

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY AND
REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS, T. 33 N., R. 58 E.

CHAINS

This corner is located 3 lks. S. of cor. of fences
extending N., S. 80° W. and NE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 N., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
C. C. Tracy, U. S. Deputy Surveyor, in 1868 and 1869,
And the Completion Survey by
Henry Thurtell, U. S. Compassman, in 1903.

From the cor. of secs. 35 and 36, on the S. bdy. of the
Tp.

N. 0° 26' W., bet. secs. 35 and 36.

Over mountainous terrain, through light brush and heavy
timber; desc. 820 ft. over NE. slope.

40.38

The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a
granite stone, 12x12x3 ins., mkd. $\frac{1}{4}$ on the W. face,
firmly set, protruding 6 ins. above ground, with a
mound of stone, 3 ft. base, 2 ft. high, W. of cor.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T33N R58E

$\frac{1}{4}$
S 35 | S 36

1970

bury the original corner stone alongside the iron post
and rebuild the mound of stone, 4 ft. base, 3 ft. high,
W. of cor.

N. 0° 09' E., beginning new measurement.

Descend 730 ft. over NE. slope.

24.50

Trail road, bears NW. and SE.

39.62

Point for the cor. of secs. 25, 26, 35 and 36, at propor-
tionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T33N R58E

S 26 | S 25
S 35 | S 36

1970