

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF
T. 34 N., R. 60 E.

CHAINS	
	<p style="text-align: center;">T35N R60E $\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$ T34N</p> <p style="text-align: center;">1970</p> <p>deposit the original cornerstone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 55' W., beginning new measurement.</p> <p>Asc. 10 ft. over an E. slope.</p> <p>0.90 Spur, slopes SW.; desc. 140 ft. over a W. slope.</p> <p>1.70 Fence, bears NNE. and SSW.</p> <p>9.80 Fence, bears NW. and SE.; desc. 130 ft. over a SW. slope.</p> <p>21.20 Ravine, drains SSW.; asc. slightly over SE. slope.</p> <p>22.90 Trail road, bears SE. and NW.; asc. 20 ft. over a SE. slope.</p> <p>26.80 Trail road, bears NE. and SW.; asc. slightly over a SE. slope.</p> <p>27.00 Spur, slopes NE.; desc. 270 ft. over a W. slope.</p> <p>40.64 The cor. of secs. 5, 6, 31 and 32, monumented with a granite stone, 20x11x4 ins., mkd. with 5 notches on the E. face and 1 notch on the W. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R60E S 31 S 32 S 6 S 5 T34N</p> <p style="text-align: center;">1970</p> <p>bury the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <hr/> <p>S. 89° 58' W., bet. secs. 6 and 31.</p> <p>Over mountainous terrain, through light sagebrush; desc. 20 ft. over a W. slope.</p> <p>0.30 Fence, bears NNE. and SSW.; desc. slightly over a W. slope.</p>