

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF  
T. 34 N., R. 60 E.

CHAINS		
35.80	Powerline, bears S. $6\frac{1}{2}^{\circ}$ E. and N. $6\frac{1}{2}^{\circ}$ W.	
39.89	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.  T34N R60E S 5 <sup><math>\frac{1}{2}</math></sup>   S 4  1970	
40.10	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.  Creek, 10 lks. wide, 1 ft. deep, course WSW.	
44.30	The SE. cor. of ranch house, bears E., 0.76 chs. dist., asc. 470 ft. over SW. slope.	
80.08	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.  The cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 6 ft. base to top, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., with brass cap mkd.  T34N R60E S 31   S 32  1917	
	N. $0^{\circ} 08'$ W., bet. secs. 31 and 32.  Over mountainous terrain, through scattering aspen timber and dense sagebrush; asc. 260 ft. over S. slope.	
13.30	Spur, slopes ENE.; desc. 650 ft. over N. slope.	
35.50	Ravine, drains NE.; desc. 30 ft. along an E. slope.	
40.54	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	