

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 43 EAST

CHAINS	
	<p style="text-align: center;">S C T36N R43E <u>½ S 31</u></p> <p style="text-align: center;">1970</p> <p>reset the willow post and set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 57' W., beginning new measurement.</p> <p>Over nearly level land.</p>
20.80	Trail road, bears SSE. and NNW.
26.62	The N. ¼ sec. cor. of sec. 6, T. 35 N., R. 43 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 35 N., R. 43 E., concurrently resurveyed under this same Group.
40.20	The standard cor. of Tps. 36 N., Rs. 42 and 43 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.
<hr/> <p>DEPENDENT RESURVEY OF THE EAST BOUNDARY OF T. 36 N., R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA.</p> <hr/>	
<p>Reestablishment of the Survey Executed by A. J. Hatch, U. S. Deputy Surveyor, in 1868.</p> <hr/>	
	<p>From the standard cor. of Tps. 36 N., Rs. 43 and 44 E. N. 0° 16' W., bet. secs. 31 and 36.</p> <p>Over nearly level land, through greasewood and shadscale.</p>
40.13	<p>Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R43E R44E ½ S 36   S 31</p> <p style="text-align: center;">1970</p> <p>set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.</p>