

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 39 N., R. 51 E., MDM, NEVADA

CHAINS	
14.70	Fence, bears E. and W.; desc. 240 ft. over N. slope.
36.70	Fence, bears W. and E., 15 lks. to fence cor., from which fences bear E., W. and N.
39.18	The $\frac{1}{4}$ sec. cor. of sec. 18, monumented with a basalt stone, 14x10x5 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on E. face.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T39N  R51E   $\frac{1}{4}$  S 18
	1974
	deposit the original cornerstone alongside the iron post and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.
	N. 0° 18' W., beginning new measurement.
	Along fence.
1.50	Pleasant Creek, 10 lks. wide, 1 ft. deep, course E.; asc. 160 ft. over S. slope.
15.20	The closing cor. of secs. 3 and 10, T. 39 N., R. 50 E., hereinafter described; asc. slightly over S. slope.
18.20	Spur, slopes E.
19.60	Fence cor., bears E., 0.28 chs. dist., from which fences bear S. and E.; desc. 50 ft. over N. slope.
24.40	Head of ravine, drains E.; asc. 40 ft. over S. slope.
33.50	Spur, slopes E.; desc. 40 ft. over N. slope.
40.27	The cor. of secs. 7 and 18, monumented with a basalt stone, 18x12x4 ins., firmly set 10 ins. in the ground, mkd. with 4 grooves on S. face and 2 grooves on N. face.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T39N R50E R51E S 3   $\frac{S}{S}$ $\frac{7}{18}$
	1974