

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 39 N., R. 50 E., MDM, NEVADA

<p>CHAINS 40.07</p>	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a granite stone, 14x12x8 ins., firmly set 10 ins. in the ground, mkd. with 1 notch on W. edge and 5 notches on E. edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N R50E S 31 S 32 S 6 S 5 T38N</p> <p>1970</p> </div> <p>deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p>	
	<p>S. 89° 56' W., bet. secs. 6 and 31.</p>	
	<p>Over rolling land, covered with sagebrush and bunchgrass.</p>	
<p>24.50</p>	<p>Fence, bears NE. and SW.</p>	
<p>40.16</p>	<p>The ¼ sec. cor. of secs. 6 and 31, monumented with a granite stone, 18x10x10 ins., firmly set 12 ins. in the ground, mkd. ¼ on N. face, with a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N R50E S 31 ¼ ——— S 6 S 6 T38N</p> <p>1970</p> </div> <p>deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	
	<p>N. 89° 55' W., beginning new measurement.</p>	
<p>11.30</p>	<p>Draw, drains NNW.</p>	
<p>12.50</p>	<p>Midas Road, improved, bears N. and S.; asc. 30 ft. over N. slope.</p>	