

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 39 N., R. 50 E., MDM, NEVADA

CHAINS	
	Ascend 50 ft. over W. slope.
52.30	Ridge, bears E. and W.; desc. 300 ft. over N. slope.
78.76	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T39N R49E R50E S 24 S 19 S 25 S 30</p> <p style="text-align: center;">1971</p> <p>raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p>
	N. 0° 13' W., bet. secs. 19 and 24.
	Over rolling mountainous land, covered with sagebrush and bunchgrass.
1.00	Bull Camp Creek, 10 lks. wide, 1 ft. deep, course SSW.; asc. 460 ft. over ESE. slope.
39.00	Top of ascent; desc. 20 ft. along E. slope.
39.38	The ¼ sec. cor. of secs. 19 and 24, monumented with a basalt stone, 18x12x8 ins., firmly set in a mound of stone, mkd. ¼ on W. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T39N R49E R50E ¼ S 24 S 19</p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post.</p>
	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a granite stone, 30x12x8 ins., firmly set in a mound of stone, mkd. with 5 grooves on S. face and 1 groove on N. face.
	At the corner point