חווים מודים מודים	RESTRUEY	ΩŦ	۸	PORTITON	∩ਜਾ	गधक	SUBDIVISIONAL	TTMTC
	TUDOTABL	OI	Д	TOTITION	OI.	T1111	DODDIATOTOWE	وصندالاعداد
	ш ос			D 50 5			TITTE A TO A	

	T. 39 N., R. 50 E., MDM, NEVADA
chains 63.00	Trail road on spur, sloping E., trail road bears E. and W.; desc. 40 ft. over NNE. slope.
69.00	Creek, 10 lks. wide, 1 ft. deep, course SSE.; asc. 210 ft. over WSW. slope.
80.40	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. and witnessed as described in the field note record of T. 40 N., R. 50 E., resurveyed concurrently under this same group.
	The cor. of secs. 28, 29, 32 and 33, monumented with a limestone, 14x12x6 ins., firmly set in a mound of stone, mkd. with 1 groove on S. face and 4 grooves on E. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T39N R50E S 29 S 28 S 32 S 33
	1971
	deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
e e	From this corner, the cor. of secs. 27, 28, 33 and 34, hereinbefore described, bears S. 89° 38' E., 80.16 chs. dist. There is no remaining evidence of the 4 sec. cor. of secs. 28 and 33.
	N. 0° 19' W., bet. secs. 28 and 29.
	Over mountainous land, covered with sagebrush and bunch- grass; asc. 90 ft. over W. slope.
8.50	Top of ascent; desc. 390 ft. over WNW. slope.
38.30	Creek, 10 lks. wide, 1 ft. deep, course SSW.
39.06	Point for the % sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T39N R50E 光
	s 29 s 28
	1971
	This cor. is located 0.50 chs. dist. W. of creek, 10 lks.

This cor. is located 0.50 chs. dist. W. of creek, 10 lks. wide, 1 ft. deep, course SSW.