

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 39 N., R. 50 E., MDM, NEVADA

CHAINS	
50.70	Lewis Creek, 10 lks. wide, 1 ft. deep, course SW.
51.30	Trail road, bears NE. and SW.
59.90	Creek, 10 lks. wide, 1 ft. deep, course SE.; asc. 240 ft. over broken S. slope to the sec. cor.
65.50	Fence, bears NNE. and SSW. irregularly.
76.80	Fence, bears E. and W.
82.50	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. and witnessed as described in the field note record of the dependent resurvey of T. 40 N., R. 50 E., resurveyed concurrently under this same group.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.
	N. 3° 35' E., bet. secs. 31 and 32.
	Over mountainous land, covered with sagebrush and bunchgrass; desc. 80 ft. over N. slope.
13.60	Willow Creek, 10 lks. wide, 1 ft. deep, course WSW.
16.30	Fence, bears NE. and SW.
17.40	Midas Road, improved, bears E. and W.; asc. 120 ft. over S. slope.
26.20	Underground telephone line, bears N. 88½° E. and S. 88½° W.
30.00	Ridge, bears E. and W.; desc. 80 ft. over N. slope.
36.10	Rattlesnake Creek, 10 lks. wide, 1 ft. deep, course WSW.; asc. 40 ft. over S. slope.
40.75	Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T39N R50E ¼ S 31 S 32</p>
	1971
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Ascend 220 ft. over S. slope to sec. cor.
77.00	Creek, 10 lks. wide, 1 ft. deep, course SSE.