

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF R. 50 E., MDM, NEVADA

CHAINS	
8.70	Ridge, bears N. and S.; desc. 190 ft. over W. slope.
20.49	The N. $\frac{1}{4}$ sec. cor. of sec. 6, T. 40 N., R. 50 E., hereinafter described.
	Descend 240 ft. over W. slope to the $\frac{1}{4}$ sec. cor.
35.60	Draw, drains WSW.
38.85	The standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented with a granite stone, 14x8x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S C T41N R50E <u><math>\frac{1}{4}</math> S 33</u>
	1971
	deposit the original cornerstone and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.
	From this corner, a spring, bears S. $73\frac{1}{2}^{\circ}$ E., 1.25 chs. dist.
	<hr style="width: 30%; margin: auto;"/> S. $89^{\circ} 36'$ W., beginning new measurement.
	Over mountainous land.
1.50	Draw, drains NW.; asc. 50 ft. over N. slope.
18.67	The closing cor. of Tps. 40 N., Rs. 49 and 50 E., hereinafter described.
	From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 32, bears S. $89^{\circ} 36'$ W., 61.27 chs. dist., monumented with a granite stone, 14x10x8 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face. There is no remaining evidence of the original standard cor. of secs. 32 and 33.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.