

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 40 N., R. 50 E., MDM, NEVADA

CHAINS	
27.50	Ravine, 10 lks. wide, 1 ft. deep, course S.; asc. 170 ft. over E. slope.
39.13	The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, monumented with a limestone, 14x9x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T40N R50E \\ \frac{1}{4} \frac{S 32}{S 5} \\ T39N R50E \\ 1970 \end{array}$
	deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	<hr/>
	S. $89^{\circ} 35'$ W., beginning new measurement.
	Over mountainous land.
0.50	Spur, slopes S.; desc. 230 ft. over W. slope.
12.00	Ravine, drains S.; asc. 140 ft. over E. slope.
20.30	Spur, slopes S.; desc. 140 ft. over W. slope.
26.30	S. edge of spring, 1.00 ch. diam., flows SSW.
35.00	Ravine, drains S.; asc. 100 ft. over E. slope.
39.49	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. diam., $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T40N R50E \\ \frac{S 31 S 32}{S 6 S 5} \\ T39N \\ 1970 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<hr/>
	S. $89^{\circ} 35'$ W., bet. secs. 6 and 31.
	Over mountainous land, covered with medium sagebrush and bunchgrass.