

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 50 E., MDM, NEVADA

CHAINS	
11.30	Draw, drains NE.; asc. 230 ft. over NW. slope.
24.00	Spur, slopes NE.; desc. 220 ft. over E. slope.
34.00	Draw, drains SSE.; asc. 100 ft. over W. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at record distance from the cor. of secs. 27, 28, 33 and 34; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T40N R50E</p> <p>$\frac{1}{4}$ $\frac{S\ 27}{S\ 34}$</p> <p>1974</p> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Ascend 20 ft. over W. slope.</p>
43.50	Spur, slopes SSE.; desc. 430 ft. over E. slope.
98.05	<p>Intersect the W. bdy. of sec. 6, T. 39 N., R. 51 E.</p> <p>The closing cor. of secs. 27 and 34, monumented with a granite stone, 16x12x6 ins., firmly set 8 ins. in the ground, mkd. with 5 grooves on N. face, 1 groove on S. face and 4 grooves and CC on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T40N R39E</p> <p>R50E R51E</p> <p>CC $\frac{S\ 27}{S\ 34}$ S 6</p> <p>1974</p> </div> <p>deposit the original cornerstone alongside the iron post.</p> <p>From this corner, the $\frac{1}{4}$ sec. cor. of sec. 6, T. 39 N., R. 51 E., bears S. $0^{\circ} 13'$ W., 16.15 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field note record of T. 39 N., R. 50 E., resurveyed concurrently under this same group.</p>